



## Specifications

Capacity Tonnes	Span mms.	End Projection mms.	Hook DSL Side mms.	Approach OPP Side mms.	Head Room mms.	Wheel Base mms.	Girder Projection Below Rail mms.	Driver Cabin Below Rail mms.	Weight of Crane Tonnes	Max Wheel Load Tonnes
	S	A	E	F	C		K	L		
5.0	10500	250	1000	850	1700	3600	200	2300	10.2	6.0
	13500	250	1000	850	1750	3800	250	2350	11.5	6.1
	16500	250	1100	900	1800	4000	250	2350	12.3	6.6
	20000	270	1100	900	1900	4200	300	2400	13.7	6.9
	22500	270	1100	900	1900	4200	300	2400	15.7	7.5
10.0	10500	250	1000	850	1800	3800	250	2350	13.2	9.5
	13500	250	1000	900	1900	4000	300	2400	14.7	10.0
	16500	250	1100	900	1900	4200	300	2400	16.4	10.5
	20000	270	1100	900	2000	4600	300	2400	18.5	11.8
	22500	270	1100	900	2000	4800	300	2400	21.0	12.3
15.0	10500	270	1100	900	1900	4200	250	2350	15.8	13.4
	13500	270	1200	1000	1900	4600	300	2400	17.6	14.1
	16500	270	1200	1000	2100	4600	300	2400	19.7	14.3
	20000	300	1300	1100	2200	4800	350	2450	22.5	15.7
	22500	300	1300	1100	2300	5200	350	2450	25.4	16.6
20.0	10500	270	1200	1000	1900	4600	250	2350	17.7	16.0
	13500	270	1200	1000	1900	4800	300	2400	19.9	16.9
	16500	300	1200	1000	2200	4800	350	2450	22.1	17.8
	20000	300	1300	1100	2400	5200	400	2500	25.2	18.7
	22500	300	1350	1100	2400	5400	400	2500	27.8	19.4
25.0	10500	270	1200	1000	2000	4600	300	2400	19.9	18.7
	13500	270	1200	1000	2000	4800	300	2400	21.9	19.2
	16500	300	1200	1000	2200	4800	350	2450	24.9	20.8
	20000	300	1300	1100	2400	5200	400	2500	27.3	21.6
	22500	300	1350	1100	2400	5400	400	2500	31.8	22.9
30.0	10500	270	1200	1000	2000	4600	300	2400	23.3	23.2
	13500	270	1200	1000	2000	4800	300	2400	26.3	24.6
	16500	300	1200	1000	2200	5200	350	2450	28.1	25.6
	20000	300	1300	1100	2400	5400	400	2500	31.1	26.2
	22500	300	1350	1100	2400	5600	400	2500	36.0	28.1

- NOTE: 1. All dimensions are in mm  
 2. Above specifications are for Class II (M 5) duty cranes, with 6.0 meter height of lift.  
 3. Above are our standard parameters. Cranes could be manufactured to suit customers requirement.  
 4. Dimensions above 30 Tonnes capacity can be provided on request.  
 5. We reserve the right to modify weights and dimensions.